


Floorline Water Polo




Slip-resistant poolside matting with brightly colored field markings.



Define your water polo field quickly and easily with Floorline Water Polo, a tri-colored roll that's seamless to install, light to carry and easy to store.

The mat's etched surface provides excellent slip resistance, while the open grid with channelled bars delivers the highest level of drainage, ensuring the poolside remains safe for players and referees. Anti-microbial and anti-fungal additives keeps the mat hygienic and protects bare feet.



Features:



Etched pattern



Open-grid construction



Anti-microbial and anti-fungal additives




UV resistant



Comes in one 49' roll

Colors:



Red/yellow/green

Benefits:



Certified slip resistant
(DIN 51130:RI I,
DIN 51097:C,
ASTM I677: I.0/0.8)



Excellent drainage



Excellent hygiene,
easy to clean



Can be used indoor
and outdoor



Quick to install

Plastex Matting Inc.

120 55th St NE
Fort Payne, AL 35967
+1 256 845 7725

USA + UK manufactured
matting products:
plastexmatting.com

Floorline Water Polo

Data sheet



Standard sizes:

Product	Floorline Water Polo
Height	1/4" (6mm)
Standard roll options	49' x 2' (15 x 0.6m) 49' x 3' (15 x 0.91m)
Weight	0.76 lb/sq.ft (3.7 kg/m ²)

Tolerances:

	Height (+/- 0.05")	Length (0+1.0')	Width (+/- 1/2")
Floorline Water Polo	1/4"	49'	2' 3'

All dimensions are nominal

Technical information:

Acoustic	Excellent sound absorption
Chemical	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this information sheet .
Composition	Flexible Polyvinyl Chloride (PVC)
Environment	Floorline Water Polo is 100% recyclable. We don't use any substances included in the SVHC list under REACH in any of our matting products..
Fire	DIN 4102 Part 1- Classification B2. BS 2782 Part 1, method 140A: 1992 (ISO 1210: 1992)
Hygiene	Made from non-porous PVC that's naturally resistant to bacteria growth.
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by downloading this information sheet .
Slip resistance	ASTM F 1677 - Dry/Wet: 1.0/0.8 DIN 51097: Classification C
Thermal	Designed to function at temperatures from -7°F and up to +140°F. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation. The red colour isn't colourfast in direct sunlight.
Warranty	One year. Visit our policies page for more information about warranties

Installation:

Floorline Water Polo's one-piece construction means installation is simple:

- Comes in 49' rolls
- Lightweight, easy to move and carry
- Contours to uneven surfaces

Cleaning:

Keeping Floorline Water Polo looking good is easy:

- Light to handle; simply roll or lift to clean
- No special cleaning tools needed
- Easy to clean with a pressure hose
- Anti-microbial and anti-fungal additives ensure excellent hygiene