

## Cleaning guidance

The following cleaning and maintenance procedure is recommended to ensure the product maintains its desired appearance and performance, as well as ensuring a long life span. If the entrance mat is neglected and allowed to become saturated in dirt and debris it will prove more difficult to restore to its original condition. We recommend attending to Frontrunner SB+ as a part of a daily cleaning procedure, the simplicity of cleaning regime ensures this can be done in a timely manner, without need to alter current procedure.

### Preparation

#### Equipment required:



**Vacuum cleaner\***  
(Minimum power 1200W)



**Coarse brush**  
(or blunt instrument)



**Mop**  
(or damp cloth)

\* Industrial cleaner recommended, preferably with a driven brush to the pile of the absorbent inserts.

### Cleaning procedure

- 1) Vacuum top surface of mat thoroughly. Frontrunner SB+ is manufactured at 6mm depth with a solid back to ensure that dirt trapped within matting channels is contained in an easily accessible area for vacuuming.
- 2) Remove any solid debris wedged between channels using coarse brush.
- 3) Wipe clean PVC scraper bars using damp cloth/sponge or mop. This will return PVC to original colour.
- 4) If cleaning a surface mounted module mat, wipe PVC edging with a cloth to clean.

### Chewing gum and stain removal

It is important to remove heavy stains and chewing gum as they appear. Heavy stain and specific chewing gum remover to be used in this event; failure to remove staining quickly will attract further dirt and reduce capability of maintaining mat to original condition.