

Gateway SB+ (Frontrunner SB+)



Solid-backed entrance matting with carpet inserts for maximum moisture removal in internal areas.



The superhero of the entrance matting world, Gateway SB+ is a low-profile, solid-backed mat that requires no recessed mat well.

Simply roll out, cut to fit and lay within your existing carpet tiles or luxury vinyl tiles – no mat well needed. You can also place directly on your current floor with ramped PVC edges to create a slip-resistant walkway. The mat's etched pattern removes debris and the heavy-duty absorbent inserts dries any moisture, helping to reduce the amount of dirt walked into the building. Wheel-and-heel proof with excellent rolling resistance, it's perfect for commercial buildings and shopping centers with high traffic.



Features:



Etched pattern



One layer hollow construction



Ribbed vinyl pattern with solid backing



6.5mm grid height



Close mesh grid



Benefits:



Certified slip resistant (DIN 51130: R1 I, ASTM C1028: 0.6/0.6)



Light to handle



Easy to install, no need for recessed mat well



Loose lay or adhere to subfloor



Wheel-and-heel proof



Plastex Matting Inc.

120 55th St NE
Fort Payne, AL 35967
+1 256 845 7725

USA + UK manufactured matting products:
plastexmatting.com

Data sheet

Standard sizes:

Product	Gateway SB+
Height	6.5/8mm (1/4"-5/16")
Standard roll options	10 x 1m (33' x 3'3")
Standard module option	1 x 1.5m (3'3" x 4'11")
Weight	6.3 kg/m ² (1.3lb/sq.ft)

Surface modules are supplied with factory fitted PVC ramped edging to four sides

Tolerances:


	Height (+/- 0.5mm)	Length (0+0.3m)	Width (0+2cm)
Gateway SB+	6.5/8 mm	10 m	100 cm

All dimensions are nominal

Colours:



Black



Grey

More colours available upon request


Carpets:



Black 608



Dark grey 607



Grey 606

Ancillaries:

PVC edging (SB / SB+)



Supplied in rolls of 60m (197") length. One tube of cold welding paste recommended for every 10m of edging. Comes in black and dark grey. Size: 6.5mm x 30mm x 60m (1/4" x 1" x 197")

PVC joining strip (SB / SB+)



Can be welded to join rolls end-to-end or side-to-side when doing large installations. Comes in black. Size: 3.5mm x 3.6m (1/8" x 11'9")

Product data sheet

PVC backing technical information:

Acoustic	Excellent sound absorption
Chemical	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this information sheet
Composition	Flexible Polyvinyl Chloride (PVC)
Environment	We don't use any substances included in the SVHC list under REACH in any of our matting products.
Fire	EN ISO 13501-1:2007-Cfl-S1, ASTM E648 – Class 2
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by downloading this information sheet .
Rolling resistance	ASTM F 2753: 0.080in loss of thickness after 1,000 cycles at 500lb
Slip resistance	ASTM E303 Dry/Wet with lines along-lines across 74-95 / 61-74 DIN 51130: R11, V10
Thermal	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation
Warranty	Three years. Visit our policies page for more information about warranties

Absorbent inserts (Zeno 600 series) technical information:

Wear classification	EN 1307 - 33, Commercial heavy
Pile material	ECONYL®, 100% regenerated polyamide BCF
Tuft base	100% regenerated non woven polyester Colback™
Phthalate Free backing	Waterproof Comfort™ vinyl
Total height	EN 1765 ± 8.7 mm
Pile height	EN 1766 ± 6.7 mm
Total weight	EN 8543 ± 4260 g/m ²
Pile yarn weight	± 820 g/m ²
Pile density	± 0,127 g/cm ³
Fire	EN ISO 13501-1:2007 Cfl-S1
Suitable for castor chairs	EN 985 A, intensive use r=2.8
Colours	5

Installation:

Gateway SB+'s one-piece construction means installation is simple. There are two ways to install SB+: adhere or loose lay. For large installations with medium to high traffic, we recommend adhering your mat.

[Watch](#) or [download](#) the installation instructions.

Cleaning:

Keeping Gateway SB+ looking good is easy:

- Lightweight
- Simply roll or lift to clean
- No special tools needed
- Quick and easy to vacuum

[Watch](#) or [download](#) the cleaning instructions.